



CHARGER SPECIFICATIONS

Model No: PC-6150M
AC Input Range: 90 to 260VAC; 50-60Hz
Battery Charge Voltage: 4.2VDC max. per position
Battery Charge Current: 4A max., per position
Battery Connection: Contacts
Led Indicators: Flashing green LED – Charging Solid green LED – Fully Charged Flashing red LED – Error Solid red LED – Waiting for Charging to Start
Weight: 28 lbs. (13 Kg)
Dimensions: 20" x 16 3/4" x 10 1/4" H (51cm x 43cm x 26cm)
Battery Charging Temp: 0°C to +45°C (+32°F to +113°F)
Operating Temp: -20°C to +50°C (-4°F to +122°F)
Storage Temp: -40°C to +70°C (-40°F to +158°F)
Operating Altitude: 27,000 ft. (8,229.6 m)
Storage Altitude: 55,000 ft. (16,764 m)
Humidity: 95% relative
Color: Black
Exterior Carrying Case: Hard plastic case
Harmonized Tariff Code: 8504.40.9550

TYPICAL APPLICATIONS

- Charging for remote, field and depot settings
- Lithium Ion Batteries

KEY FEATURES

- Simultaneous charging
- LED display for each battery charging position
- 15-position battery charging capability
- Unattended charging
- Tactical, portable
- Rugged, environment resistant case
- Manufactured under ISO 9001:2008 certified quality system

BENEFITS

- Charges up to 15 batteries simultaneously
- Easy battery connection – no cables required
- Batteries contained in charger for charge cycle duration

CHARGES THE FOLLOWING BATTERIES

- **Lithium Ion**
 - PB-1301 • PB-1601 • PBH-1301 • PBH-1601